

Package: mlmtools (via r-universe)

September 18, 2026

Title Multi-Level Model Assessment Kit

Version 1.1.0

Maintainer Laura Jamison <lj5yn@virginia.edu>

Description Multilevel models (mixed effects models) are the statistical tool of choice for analyzing multilevel data (Searle et al, 2009). These models account for the correlated nature of observations within higher level units by adding group-level error terms that augment the singular residual error of a standard OLS regression. Multilevel and mixed effects models often require specialized data pre-processing and further post-estimation derivations and graphics to gain insight into model results. The package presented here, 'mlmtools', is a suite of pre- and post-estimation tools for multilevel models in 'R'. Package implements post-estimation tools designed to work with models estimated using 'lme4's (Bates et al., 2014) lmer() function, which fits linear mixed effects regression models. Searle, S. R., Casella, G., & McCulloch, C. E. (2009, ISBN:978-0470009598). Bates, D., Mächler, M., Bolker, B., & Walker, S. (2014) <doi:10.18637/jss.v067.i01>.

Depends R (>= 3.5.0)

Imports lme4,stats,ggplot2

License GPL (>= 3)

Encoding UTF-8

LazyData true

RoxygenNote 7.2.1

Config/pak/sysreqs cmake make

Repository <https://lkjamison.r-universe.dev>

Date/Publication 2023-02-14 20:43:31 UTC

RemoteUrl <https://github.com/lkjamison/mlmtools>

RemoteRef HEAD

RemoteSha a6bb2233c3460373eb7d62479f6b248b91af7e7d

Contents

betweenPlot	2
caterpillarPlot	3
center	4
ICCM	5
instruction	7
levelCompare	8
levelComparePlot	9
mlm_assumptions	10
prints	11
reporting	12
rsqmlm	13
varCompare	14
withinPlot	15
Index	17

betweenPlot	<i>Plots Between Group Associations</i>
-------------	---

Description

Plots the between-group associations between an outcome and predictor variable.

Usage

```
betweenPlot(  
  x,  
  y,  
  grouping,  
  dataset,  
  xlab = x,  
  ylab = y,  
  between_title = "Between-Group Association Plot",  
  point_color = "gray40",  
  line_color = "black",  
  se = FALSE,  
  full_range = FALSE,  
  lty = 1,  
  linewidth = 2  
)
```

Arguments

- | | |
|----------|---------------------|
| x | Predictor variable. |
| y | Outcome variable. |
| grouping | Grouping variable. |

dataset	A dataset containing the predictor, outcome, and grouping variables.
xlab	Character vector specifying the horizontal axis label.
ylab	Character vector specifying the vertical axis label.
between_title	Character vector specifying the title for the between group plot.
point_color	Color for points.
line_color	Color for lines.
se	A logical value indicating whether confidence intervals should be displayed.
full_range	A logical value indicating whether the fit line should span the full range of the plot or just the data.
lty	Line type.
linewidth	Width of fit line.

Value

Produces a plot of the between-group associations between an outcome and predictor variable.

References

Chow, S., Gilmore, R. O., Hallquist, M., Ram, N., & Brinberg, M. (2019). Introduction to multilevel model and interactions. GitHub. https://github.com/psu-psychology/r-bootcamp-2019/blob/master/talks/RBootcamp_MLMI

Examples

```
# Read in data
data(instruction)
# Produce between plot
betweenPlot(x = "mathkind", y = "mathgain", grouping = "classid",
dataset = instruction, xlab = "Kindergarten Math Score",
ylab = "Gain in Math Score")
```

caterpillarPlot	<i>Caterpillar Plot</i>
-----------------	-------------------------

Description

Plots empirical Bayes both point prediction and prediction intervals for each random effect parameter across all groups.

Usage

```
caterpillarPlot(
  model,
  grouping,
  title = print(grouping),
  tall = TRUE,
  grey = FALSE
)
```

Arguments

model	A given lmer model.
grouping	The name of the grouping variable of interest, as a character string.
title	The title of the plot.
tall	Logical argument specifying whether the plot should be plotted vertically or horizontally.
grey	Logical argument specifying whether the intervals should be plotted in color or greyscale.

Value

Produces a caterpillar plot.

References

Rabe-Hesketh S, Skrondal A (2012). Multilevel and Longitudinal Modeling Using Stata, Volumes I and II, Third Edition. 3 edition edition. Stata Press. ISBN 978-1-59718-108-2.

Examples

```
# Read in data
data(instruction)
# Create model
mod <- lme4::lmer(mathgain ~ (1 | classid), data = instruction)
# Produce caterpillar plot
caterpillarPlot(mod, title = "title", grouping = "classid", grey = TRUE)
```

center

Centers variables for mixed effects models

Description

Centers variables using the group-mean (person-mean) centering approach for mixed-effects models, and adds these variables to the data frame.

Usage

```
center(
  dataset,
  x,
  grouping,
  type = "mean",
  standardize = FALSE,
  centerResult = FALSE
)
```

Arguments

dataset	A dataset containing the variables to be centered and the grouping variable
x	The variable or variables to be centered
grouping	The variable or variables that define the grouping structure of the data
type	a function to compute the grouping summary variable
standardize	a logical value indicating whether x should be standardized before the computation proceeds
centerResult	a logical value indicating whether resulting grouping summary variable values should be centered at 0

Value

Creates two new variables in the data frame - a mean of the desired variable computed for each unique value in the grouping variable and a deviation score for each observation within the grouping variable that is that observation's raw score subtracted from the group mean.

References

Enders, C. & Tofighi, D. (2007). Centering predictor variables in cross-sectional multilevel models: A new look at an old problem. *Psychological Methods*, 12(2), 121–138

Examples

```
data(instruction)
#Center student level socioeconomic status, "ses", around class mean "ses"
### To repress output: use invisible()
center(dataset = instruction, x = "ses", grouping = "classid")
#Center class-level variable teacher's mathematic preparation,
# mathprep, around school mean "mathprep"
center(dataset = instruction, x = "mathprep", grouping = "schoolid")
```

ICCM

Computes ICC values for mixed-effects models

Description

Computes ICC values for lme4-fitted mixed-effects models.

Usage

```
ICCM(model, re_type = c("NA"))
```

Arguments

<code>model</code>	A linear mixed-effects model of class <code>lmerMod</code> , <code>lmerModLmerTest</code> , or <code>glmerMod</code> of type binomial
<code>re_type</code>	A value indicating whether a model with two random effects is nested or cross-classified

Value

If `re_type` is "NA", the proportion of variance at the random effect is computed.

If `re_type` = "nested", the likeness of y scores in the same level 3 unit (the proportion of variance at `Level3_factor`), the likeness of y scores in the same level 2 units in the same level 3 unit (proportion of variance at `Level3_factor` and `Level2_factor`), and the likeness of level 2 units in the same level 3 unit (proportion of `Level2_factor` variance at `Level3_factor`) are computed.

If `re_type` = "cc", the likeness of y scores in the same `C1_factor` unit (correlation between outcome values of units in same `C1_factor` but different `C2_factor`), the likeness of y scores in the same `C2_factor` (correlation between outcome values of units in the same `C2_factor` but different `C1_factor`), and the likeness of y scores in the same `C1_factor` and `C2_factor` combination (correlation between outcome values of units in the same `C2_factor` and `C1_factor`) are computed.

References

Snijders, T. A. B. & Bosker, R. J. (2012). *Multilevel Analysis* (2nd Ed.). Sage Publications Ltd.
 Goldstein, H., Browne, W., & Rasbash, J. (2002). Partitioning variation in multilevel models. *Understanding statistics: statistical issues in psychology, education, and the social sciences*, 1(4), 223-231.

Examples

```
# Gaussian
## Read in data
data(instruction)
## Create model
mod <- lme4::lmer(mathgain ~ (1 | classid), data = instruction)
## Estimate ICC
ICCM(mod)

# Logistic
## Read in data
data(reporting)
## Create model
mod <- lme4::glmer(mention.outliers ~ Basics + (1 | Journal), data = reporting, family = "binomial")
## Estimate ICC
ICCM(mod)
```

instruction

Instruction Data

Description

Data from a study on instructional improvement across 312 classrooms.

Usage

```
data(instruction)
```

Format

A data frame with 1190 observations on the following 8 variables.

female Dummy variable for being female

mathkind Math achievement score in the spring of kindergarten

mathgain Gain in math achievement score from spring of kindergarten to spring of first grade

ses Socioeconomic status

mathprep First grade teacher's mathematic preparation (based on number of courses taken)

classid Classroom identifier

schoolid School identifier

childid Student identifier

Source

Stata Press

References

Rabe-Hesketh, Sophia, and Brian Everitt. Handbook of statistical analyses using Stata. CRC Press, 2003.

Hill, H. C., Rowan, B., & Ball, D. L. (2005). Effects of teachers' mathematical knowledge for teaching on student achievement. American educational research journal, 42(2), 371-406.

Examples

```
data(instruction)
```

levelCompare	<i>Reports on a comparison of the mixed model vs. a model that does not account for nesting</i>
--------------	---

Description

Uses AIC and BIC to compare whether the model that accounts for the correlation of responses within the same unit fits the data better than a model that assumes 0 correlation between responses within the same unit.

Usage

```
levelCompare(model)
```

Arguments

model	A linear mixed-effects model of class lmerMod or lmerModLmerTest
-------	--

Value

Computes the AIC and BIC of the requested model and a model with the same predictors but absent the random intercept(s) and slope(s).

References

Burnham, K. P., & Anderson, D. R. (2004). Multimodel inference: understanding AIC and BIC in model selection. *Sociological methods & research*, 33(2), 261-304. Raftery, A. E. (1995). Bayesian model selection in social research. *Sociological methodology*, 111-163.

Examples

```
data(instruction)
mod <- lme4::lmer(mathgain ~ (1 | classid), data = instruction)
levelCompare(mod)
```

levelComparePlot	<i>Plots comparison of accounting for nesting vs. not accounting for nesting</i>
------------------	--

Description

Plots the line of best fit for the relationship between two variables accounting for nesting and not accounting for nesting.

Usage

```
levelComparePlot(
  model,
  x,
  y,
  grouping,
  dataset,
  paneled = TRUE,
  select = c("select"),
  center = FALSE,
  xlab = x,
  ylab = y,
  glab = grouping,
  plot_titles = c("Scatter Plot", "Scatter Plot by Group")
)
```

Arguments

model	A linear mixed-effects model of class lmerMod or lmerModLmerTest.
x	Predictor variable.
y	Outcome variable.
grouping	Grouping variable.
dataset	A dataset containing the predictor, outcome, and grouping variables.
paneled	A logical value indicating whether the plot accounting for nesting should be split into panels.
select	A vector indicating the index of the groups to be included in the plots.
center	A logical value indicating whether the x variable should be centered
xlab	Character vector specifying the horizontal axis label.
ylab	Character vector specifying the vertical axis label.
glab	Character vector specifying the legend title for the plot accounting for nesting.
plot_titles	Character vectors specifying the titles for the plots.

Examples

```
# Gaussian
## Read in data
data(instruction)
## Create model
mod <- lme4::lmer(mathgain ~ mathkind + (1 | classid), data = instruction)
## Generate plots
levelComparePlot(mod, x = "mathkind", y = "mathgain", grouping = "classid", dataset = instruction)

# Logistic
## Read in data
data(reporting)
reporting$final.sample.size <- scale(as.numeric(reporting$final.sample.size))
reporting$mention.outliers <- ifelse(reporting$mention.outliers=="No",0,1)
mod <- lme4::glmer(mention.outliers ~ final.sample.size +
(1 | Journal), data = reporting, family = "binomial")
levelComparePlot(mod, x = "final.sample.size", y = "mention.outliers",
grouping = "Journal", dataset = reporting, paneled = FALSE)
```

mlm_assumptions

Reports the output of testing all assumptions for a multilevel model

Description

Reports the results from testing all assumptions of a multilevel model and provides suggestions if an assumption is not passed

Usage

```
mlm_assumptions(model, re_type = c("NA"))
```

Arguments

model	A linear mixed-effects model of class <code>lmerMod</code> , <code>lmerModLmerTest</code> , or <code>glmerMod</code> of type binomial.
re_type	A value indicating whether a model with two random effects is nested or cross-classified

Value

If `re_type` is "NA", the proportion of variance at the random effect is computed.

If `re_type` = "nested", the likeness of y scores in the same level 3 unit (the proportion of variance at `Level3_factor`), the likeness of y scores in the same level 2 units in the same level 3 unit (proportion of variance at `Level3_factor` and `Level2_factor`), and the likeness of level 2 units in the same level 3 unit (proportion of `Level2_factor` variance at `Level3_factor`) are computed.

If `re_type = "cc"`, the likeness of y scores in the same `C1_factor` unit (correlation between outcome values of units in same `C1_factor` but different `C2_factor`), the likeness of y scores in the same `C2_factor` (correlation between outcome values of units in the same `C2_factor` but different `C1_factor`), and the likeness of y scores in the same `C1_factor` and `C2_factor` combination (correlation between outcome values of units in the same `C1_factor` and `C2_factor`) are computed.

Tests the relevant assumptions of the specified multilevel model.

References

Glaser, R. E. (2006). Levene's Robust Test of Homogeneity of Variances. Encyclopedia of Statistical Sciences. 6.

Examples

```
# Gaussian
## Read in data
data(instruction)
## Create model
mod <- lme4::lmer(mathgain ~ mathkind + (1 | classid), data = instruction)
## Evaluate assumptions
mlm_assumptions(mod)

# Logistic
## Read in data
data(reporting)
## Create model
mod <- lme4::glmer(mention.outliers ~ Basics + (1 | Journal), data = reporting, family = "binomial")
## Evaluate assumptions
mlm_assumptions(mod)
```

prints

S3Methods for Printing

Description

Prints for `mlmtools` objects

Usage

```
## S3 method for class 'center'
print(x, ...)

## S3 method for class 'ICCM'
print(x, ...)

## S3 method for class 'rsqmlm'
print(x, ...)
```

```
## S3 method for class 'varCompare'
print(x, ...)

## S3 method for class 'levelCompare'
print(x, ...)
```

Arguments

- x Object from mlmtools package
- ... Additional arguments

Value

Prints mlmtools object

reporting	<i>Reporting Data</i>
-----------	-----------------------

Description

Data from a study on the reporting rates of outliers with data on 2235 experiments.

Usage

```
data(reporting)
```

Format

A data frame with 2235 observations on the following 18 variables.

Reference.Code Bibtex reference code for the article

year Year of publication

time.pulled Year article was pulled for these data

Type Type of psychological journal

Journal Journal of publication

authors Authors

article Title of article

original.sample.size Original sample size from the article

mention.outliers Whether or not the article mentioned outliers

final.sample.size Final sample size from the article

number.outliers Number of outliers identified by the article

Basics Whether or not they ran basic statistics (e.g., descriptive statistics, z scores, t tests, and correlations)

ANOVA Whether or not they ran ANOVA
 Regression Whether or not they ran a regression
 ChiSquare Whether or not they ran a chi-squared test
 Nonparametric Whether or not they ran a nonparametric test
 Modeling Whether or not they used structural equation modeling
 BayesOther Whether or not they used Bayes or another form of analysis

Source

[GitHub](#)

References

Valentine, K. D., Buchanan, E. M., Cunningham, A., Hopke, T., Wikowsky, A., & Wilson, H. (2021). Have psychologists increased reporting of outliers in response to the reproducibility crisis?. *Social and Personality Psychology Compass*, 15(5), e12591.

Examples

```
data(reporting)
```

rsqmlm	<i>Calculates R-squared from lmer models</i>
--------	--

Description

Calculates variance explained by lme4-fitted mixed-effects models.

Usage

```
rsqmlm(model, by_cluster = FALSE)
```

Arguments

model	A linear mixed-effects model of class lmerMod or lmerModLmerTest
by_cluster	Logical, if TRUE returns variance explained at each level

Value

Computes the percent variance explained by the model.

References

Nakagawa, S., Johnson, P. C., & Schielzeth, H. (2017). The coefficient of determination R^2 and intra-class correlation coefficient from generalized linear mixed-effects models revisited and expanded. *Journal of the Royal Society Interface*, 14(134), 20170213.

Examples

```
# Gaussian
## Read in data
data(instruction)
## Center mathkind by classid
center(dataset = instruction, x = "mathkind", grouping = "classid")
## Create model
mod <- lme4::lmer(mathgain ~ classid_mathkind.cmn +
  classid_mathkind.devcmn + (1 | classid), data = instruction)
## Calculate r-squared
#### To repress output: use invisible()
rsq <- rsqmlm(mod)
rsq
rsq$marginal
rsq$conditional

# Logistic
## Read in data
data(reporting)
## Create model
mod <- lme4::glmer(mention.outliers ~ Basics + (1 | Journal), data = reporting, family = "binomial")
## Calculate r-squared
#### To repress output: use invisible()
rsq <- rsqmlm(mod)
rsq
rsq$marginal
rsq$conditional
```

varCompare

Compares variance explained for two mixed effects models

Description

Compares variance explained by additional fixed effects for two lme4-fitted mixed-effects models.

Usage

```
varCompare(model1, model2)
```

Arguments

model1	A linear mixed-effects model of class lmerMod or lmerModLmerTest
model2	A linear mixed-effects model of class lmerMod or lmerModLmerTest

Details

Specifically, 1-(total variance for less parsimonious model/total variance for more parsimonious model).

Value

Computes the percent increase in variance explained by the less parsimonious (more complicated) model compared to the more parsimonious (less complicated) model.

References

Snijders, T. A. B. & Bosker, R. J. (2012). *Multilevel Analysis* (2nd Ed.). Sage Publications Ltd.

Examples

```
# Read in data
data(instruction)
# Create null model
mod0 <- lme4::lmer(mathgain ~ (1 | classid), data = instruction)
# Create model of interest
mod1 <- lme4::lmer(mathgain ~ mathkind + (1 | classid), data = instruction)
# Compare variance explained
### To repress output: use invisible()
varCompare(mod0, mod1)
```

withinPlot

Plots Within Group Associations

Description

Plots the within-group associations between an outcome and predictor variable.

Usage

```
withinPlot(
  x,
  y,
  grouping,
  dataset,
  xlab = x,
  ylab = y,
  within_title = "Within-Group Association Plot",
  point_color = "gray40",
  line_color = "black",
  se = FALSE,
  full_range = FALSE,
  lty = 1,
  linewidth = 2
)
```

Arguments

x	Predictor variable.
y	Outcome variable.
grouping	Grouping variable (individual may be grouping variable).
dataset	A dataset containing the predictor, outcome, and grouping variables.
xlab	Character vector specifying the horizontal axis label.
ylab	Character vector specifying the vertical axis label.
within_title	Character vector specifying the title for the within group plot.
point_color	Color for points.
line_color	Color for lines.
se	A logical value indicating whether confidence intervals should be displayed.
full_range	A logical value indicating whether the fit line should span the full range of the plot or just the data.
lty	Line type.
linewidth	Width of fit line.

Value

Produces a plot of the within-group associations between an outcome and predictor variable.

References

Chow, S., Gilmore, R. O., Hallquist, M., Ram, N., & Brinberg, M. (2019). Introduction to multilevel model and interactions. GitHub. https://github.com/psu-psychology/r-bootcamp-2019/blob/master/talks/RBootcamp_MLMI

Examples

```
# Read in data
data(instruction)
# Create within plot
mathkind_withinPlot <- withinPlot(x = "mathkind", y = "mathgain",
grouping = "classid", dataset = instruction,
xlab = "Kindergarten Math Score", ylab = "Gain in Math Score")
```

Index

* datasets

- instruction, [7](#)
- reporting, [12](#)

betweenPlot, [2](#)

caterpillarPlot, [3](#)
center, [4](#)

ICcm, [5](#)
instruction, [7](#)

levelCompare, [8](#)
levelComparePlot, [9](#)

mlm_assumptions, [10](#)

print.center (prints), [11](#)
print.ICcm (prints), [11](#)
print.levelCompare (prints), [11](#)
print.rsqmlm (prints), [11](#)
print.varCompare (prints), [11](#)
prints, [11](#)

reporting, [12](#)
rsqmlm, [13](#)

varCompare, [14](#)

withinPlot, [15](#)